



FCSS2000 INDUSTRIAL FREQUENCY CONVERTER

SERIES FCSS2000

This rugged, AC/AC frequency converter system uses field proven microprocessor controlled high frequency PWM technology to generate the required output power with pure sine wave output voltage.

It is a mature design with a track record in numerous applications.

The frequency converter is built with internal power modules.

The AC/DC input stage boosts the input voltage to a higher DC voltage, which feeds the DC/AC inverter to generate the required AC output.

Built-in fans provide sufficient airflow for operation without de-rating to the specified temperature.

The high frequency conversion enables a compact construction, low weight and high efficiency.

The use of components with established reliability results in high MTBF.

The unit is manufactured at our plant under strict quality control.

APPLICATIONS

- Aviation
- Industrial Controls
- Telecom Power Plants
- Railway / Transportation
- Military Applications
- Marine
- Mining
- Oil Rigs
- Steel Mills
- Automotive / RV
- Electric Utilities and Substations
- Base Station Power
- Manufacturing Location
- OEM Applications

FEATURES

- Sine wave output voltage
- Field-proven rugged design
- Cooling by internal fans
- Filtered input and output
- Full electronic protection
- Compact size
- 2000VA of output power



Pure Sinewave



High frequency technology



Light weight, compact size



Full electronic protection



Optional Remote shutdown



Optional Extended temperature range



Optional Output fail alarm (Form C)

SPECIFICATIONS

| | |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Input Voltage | 95 - 264Vac universal input with PFC 47 ... 410Hz are standard Consult factory for other inputs |
| Input Protection | Inrush current limiting Varistor Internal safety fuse Lower voltage than the specified minimum input will not damage the unit |
| Isolation | 2250Vdc input to chassis 2250Vdc input to output |
| Output Voltage | 115Vac @ 60Hz or 400Hz/17.4A rms continuous or 230Vac @ 50Hz/ 8.7A rms continuous Output neutral is connected to the chassis internally Isolated floating output optional Consult factory for other outputs |
| Output Wave Form | Sinusoidal |
| Total Harmonic Distortion | Less than 5% at full load |
| Line Regulation | ± 0.5% max. |
| Load Regulation | Maximum ± 6% from no load to full load. A ± 2% load regulation option is available. |
| Load Crest Factor | 2.5 at 90% load |
| Output Ripple Noise | High frequency ripple is less than 500mVrms (20MHz BW) |
| Efficiency | Depends on input and output voltage combination. Typically 78% at full load |
| Output Overload Protection | Current limiting with short circuit protection Thermal shutdown with automatic recovery in case of insufficient cooling |
| Output Overvoltage Protection | 140Vac (for 115Vac output) or 280Vac (for 230Vac output) by internal supply voltage limiting |

| | |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards | Designed to meet C22.2 No. 107.1 - 01, UL 458, EN 60950, EN 62368-1 and CE |
| EMI | EN 55032 Class A as a minimum |
| Operating Temperature | 0 to +50°C for full specification without derating Derating linearly 2.5% per °C rise above +50°C to +70°C max. Extended temperature range available on request |
| Humidity | 5 - 95% non-condensing |
| Temperature Drift | 0.05% per °C over operating temperature range |
| Cooling | Built-in fans draw air into the unit |
| Environmental Protection | Basic ruggedizing Full ruggedizing and conformal coating as option |
| Shock/Vibration | IEC 61373 Cat 1 A&B |
| Dimensions | 3U7: 3U x 19" rack-mount or chassis mount assembly 432 x 132 x 407 mm (W x H x L) including connectors |
| Weight | 14 Kg |
| Connections | Input: terminal block Output: standard AC receptacle Option: compression type terminal block |
| MTBF | 90,000 hours at 45°C Demonstrated MTBF is significantly higher Fans excluded |
| Indicators | None |
| Control Input | None Remote shutdown as option |
| Alarm output | None Optional output Fail Alarm (Form C) |
| RoHS Compliance | Fully compliant |
| Warranty | 2 years |

