



## RISI1000 INDUSTRIAL SINEWAVE INVERTER

### SERIES RISI1000

This rugged DC/AC inverter uses field proven, microprocessor controlled high frequency PWM technology to generate 1000VA output power with pure sine wave output voltage.

The inverter is built with internal power modules. The DC/DC input stage boosts the input voltage to a higher DC voltage, which feeds the DC/AC inverter to generate the required AC output.

The use of high frequency conversion enables a compact construction, low weight and high efficiency.

The input and output are filtered for low noise.

Two high quality built-in fans provide sufficient airflow for operation without de-rating to the specified temperature.

Full electronic protection, generous design headroom and the exclusive use of components with established reliability also contribute to high MTBF.

The unit is manufactured at our plant under strict quality control.

### APPLICATIONS

- Industrial Controls
- Mining
- Oil Rigs
- Steel Mills
- Marine & other rugged environments
- Automotive / RV
- Electric Utilities and Substations
- Base Station Power
- Telecom Power Plants
- Railway / Transportation
- Military Applications
- Manufacturing Location
- OEM Applications

### FEATURES

- Sine wave output voltage
- Up to 250Vdc input voltage
- Field-proven rugged design
- Cooling by internal fans
- Filtered input and output
- Full electronic protection
- Compact size
- 1000VA of output power



Pure Sinewave



High frequency technology



Light weight, compact size



Full electronic protection



Optional Remote shutdown



Optional Extended temperature range



Optional Output fail alarm (Form C)

# SPECIFICATIONS

Input Voltage	24Vdc 36Vdc 48Vdc 125Vdc 250Vdc ± 15% are standard Consult factory for other inputs
Input Protection	Inrush current limiting Varistor Reverse polarity protection Internal safety fuse Lower voltage than the specified minimum input will not damage the unit
Isolation	1700Vdc input to chassis/output or corresponding to the voltage requirements
Output Voltage	230Vac @ 50Hz/4.3A rms continuous or 115Vac @ 60Hz or 400Hz/8.7A rms continuous Output neutral is connected to the chassis internally Isolated floating output optional Consult factory for other output requirements
Output Wave Form	Sinusoidal
Total Harmonic Distortion	Less than 5% at full load
Line/Load Regulation	Maximum ± 6% from no load to full load. A ± 2% load regulation option is available.
Load Crest Factor	2.5 at 90% load
Output Ripple Noise	High frequency ripple is less than 500mVrms (20MHz BW)
Efficiency	Typically 80% at full load
Output Overload Protection	Current limiting with short circuit protection Thermal shutdown with automatic recovery in case of insufficient cooling
Output Overvoltage Protection	140Vac (for 115Vac output) or 280Vac (for 230Vac output) by internal supply voltage limiting

Standards	Designed to meet C22.2 No. 107.1 - 01, UL 458 and EN 60950-1
EMI	EN 55022 Class A with margins
Operating Temperature	0 to +50°C for full specification without derating Derating linearly 2.5% per °C rise above +50°C to +70°C max. Extended temperature range available on request
Humidity	5 - 95% non-condensing
Temperature Drift	0.05% per °C over operating temperature range
Cooling	Two high quality built-in fan draws air into the unit
Environmental Protection	Basic ruggedizing Full ruggedizing and conformal coating as option
Shock/Vibration	IEC 61373 Cat 1 A&B
Dimensions	3U3: 187 x 132 x 407 mm (W x H x L) including connectors, excluding flanges
Weight	Approx. 6.5 Kg
Connections	Input: Compression-type terminal-block For 24Vdc input – threaded studs with nuts Output: 115Vac – standard AC receptacle 230Vac – IEC receptacle Compressional-type terminal block
MTBF	95,000 hours at 45°C Demonstrated MTBF is significantly higher Fan excluded
Indicators	None
Control Input	None Remote shutdown as option
Alarm output	None Optional output Fail Alarm (Form C)
RoHS Compliance	Fully compliant
Warranty	2 years

